


- Banda doble
- Gazas reforzadas
- Cinta: Poliéster alta tenacidad
- Termofijada contra la abrasión
- DIN 61360 - Según Norma EN-1492-1 Forma B
- Coeficiente de seguridad 7:1



Referencia	Ancho de cinta (mm)	Color	Long. gazas (mm)	Long. min. (mm)	Espesor (mm)
ID - 30	30	Violeta	275	1.000	6.4
ID - 40	50	Violeta	275	1.000	6.4
ID - 50/60	50	Verde	275	1.000	6.4
ID - 80/90	75	Amarillo	275	1.000	6.4
ID - 100/120	100	Gris	300	1.300	6.4
ID - 125/150	125	Rojo	400	1.400	6.4
ID - 150/180	150	Marrón	600	1.500	6.4
ID - 200/240	200	Azul	600	2.000	7.4
ID - 250/300*	250	Naranja	600	2.200	7.4
ID - 300	300	Naranja	800	2.300	7.4

## Carga máxima de utilización según el modo a elevar en Kg



Referencia	Tiro directo	En ahorcado	En "U"	0° - 45°	45° - 60°
ID - 30	1.000	800	2.000	1.400	1.000
ID - 40	1.500	1.200	3.000	2.100	1.500
ID - 50/60	2.000	1.600	4.000	2.800	2.000
ID - 80/90	3.000	2.400	6.000	4.200	3.000
ID - 100/120	4.000	3.200	8.000	5.600	4.000
ID - 125/150	5.000	4.000	10.000	7.000	5.000
ID - 150/180	6.000	4.800	12.000	8.400	6.000
ID - 200/240	8.000	6.400	16.000	11.200	8.000
ID - 250/300*	10.000	8.000	20.000	14.000	10.000
ID - 300	12.000	9.600	24.000	16.800	12.000