

- Banda sencilla.
- Gazas reforzadas
- Cinta: Poliéster alta tenacidad
- Termofijada contra la abrasión
- DIN 61360 - según Norma EN-1492-1 Forma B
- Coeficiente de seguridad 7:1



Referencia	Ancho cinta (mm)	Color	Long. Gazas (mm)	Long. Min (mm)	Espesor (mm)
IS - 30	30	Violeta	275	1.000	3.2
IS - 40	50	Violeta	275	1.000	3.2
IS - 50/60	50	Verde	275	1.000	3.2
IS - 80/90	75	Amarillo	275	1.000	3.2
IS - 100/120	100	Gris	300	1.300	3.2
IS - 125/150	125	Rojo	400	1.400	3.2
IS - 150/180	150	Marrón	600	1.500	3.2
IS - 200/240	200	Azul	600	2.000	3.7
IS - 250/300*	250	Naranja	600	2.200	3.7
IS - 300	300	Naranja	800	2.300	3.7

Carga máxima de utilización según el modo a elevar en Kg:



Referencia	Tiro directo	En ahorcado	En "U"	0° - 45°	45° - 60°
IS - 30	500	400	1.000	700	500
IS - 40	750	600	1.500	1.050	750
IS - 50/60	1.000	800	2.000	1.400	1.000
IS - 80/90	1.500	1.200	3.000	2.100	1.500
IS - 100/125	2.000	1.600	4.000	2.800	2.000
IS - 125/150	2.500	2.000	5.000	3.500	2.500
IS - 150/180	3.000	2.400	6.000	4.200	3.000
IS - 200/240	4.000	3.200	8.000	5.600	4.000
IS - 250/300*	5.000	4.000	10.000	7.000	5.000
IS - 300	6.000	4.800	12.000	8.400	6.000

