

- Material: Poliéster 100% de multifilamento continuo.
- Según norma DIN 61360 T2 A1/01.91-EN-1492-2 Forma B
- Coeficiente de seguridad 7:1



Referencia	Ancho cinta (mm)	Color	Long. Gazas (mm)	Long. Min (mm)
IRG - 1	36	Violeta	250	1.000
IRG - 2	46	Violeta	275	1.000
IRG - 3	46	Verde	275	1.000
IRG - 4	46	Amarillo	275	1.000
IRG - 5	70	Gris	275	1.000
IRG - 6	70	Rojo	300	1.000
IRG - 8	70	Marrón	400	2.000
IRG - 10	80	Azul	600	2.000
IRG - 15	115	Naranja	600	2.000
IRG - 20	135	Naranja	800	2.000
IRG - 25	135	Naranja	800	2.000

Carga máxima de utilización según el modo a elevar en Kg



Referencia	Tiro recto	En ahorcado	En "U"	0° - 45°	45° - 60°
IRG -1	1.000	800	2.000	1.400	1.000
IRG - 2	2.000	1.600	4.000	2.800	2.000
IRG - 3	3.000	2.400	6.000	4.200	3.000
IRG - 4	4.000	3.200	8.000	5.600	4.000
IRG - 5	5.000	4.000	10.000	7.000	5.000
IRG - 6	6.000	4.800	12.000	8.400	6.000
IRG - 8	8.000	6.400	16.000	11.200	8.000
IRG - 10	10.000	8.000	20.000	14.000	10.000
IRG - 15	15.000	12.000	30.000	21.000	15.000
IRG - 20	20.000	16.000	40.000	28.000	20.000
IRG - 25	25.000	20.000	50.000	35.000	25.000